

- Pre-filtration of feedstocks
- Removal of dry wash components (resins and silicates)
- Automated change over for semi-continuous filtration with cleanliness monitoring and safety features. Built-in contamination drying process.

# Automatic - BWA



Max. Operating Pressure:	150 psi (7 bar)
Max Operating Temperature:	165°F (75°C)
Support Legs:	Fixed
Lid Closure:	Swing Bolts
Max Flow:	up to 2100 gpm (7950 L/min)
Housing Material:	see below
Seals:	see below

## Specifications

### How to Build a Valid Model Number for a Schroeder BWA:

BOX 1	BOX 2	BOX 3	BOX 4	BOX 5	BOX 6	BOX 7	BOX 8	BOX 9
BWA								

**Example:** NOTE: One option per box

BOX 1	BOX 2	BOX 3	BOX 4	BOX 5	BOX 6	BOX 7	BOX 8	BOX 9	
BWA	1	1	1	3	B	0	1	F	= BWA1113B01F

## Model Code

BOX 1	BOX 2	BOX 3	BOX 4	BOX 5
<b>Filter Series</b>	<b>Sox per Side</b>	<b>Sox Size</b>	<b>Housing Material</b>	<b>Connection*</b>
BWA	1 2 3 4 6 8 10	2	1 304S 2 316S 3 316L	3 3" Flange 4 4" Flange 6 6" Flange 8 8" Flange
BOX 6	BOX 7	BOX 8	BOX 9	
<b>Seal</b>	<b>Pressure</b>	<b>Voltage</b>	<b>Documentation</b>	
B Buna N V Viton T Teflon	1 150 psi	1 110V 60Hz 2 220V 60Hz 1 Phase 3 460/230V 3 Phase 4 575V	F Function Test U U Stamp C Code Calculations M Material Certifications	