

Quality Control Accessories

This connector is required to interface with the TWS

Part Number: **VDP-177**

What's Included: (5 pole) with 5m cable

**Electrical
Connection
TWS
Accessory**



The SMART Kit Contamination monitor makes it easy to continuously monitor ISO levels in real time, showing you exactly how dirty your fuel is. This kit can be added as a retrofit to any of Schroeder's Standard Filtration Carts (MFS/MFD), Kidney Loops (KLS/KLD), Final Polishing Units (FPU/FPH) or Skids without any additional modifications. Most carts and Kidney Loops can also be ordered with the SMART Kit included.

The SMART Kit makes using our contamination monitor easy by offering plug and play installation with all the features and benefits of our TCM.

SMART Kit

Contamination Readout: ISO 4406:1999 or SAE AS4059 (D)

Maximum viscosity: 1,000 SUS

Compatibility: All petroleum based hydraulic fluids and polished biodiesel

Weight: 18.1 lbs

Power Requirement: 115VAC

Inlet pressure: <7 psi

Operating Temperature: -20° to 150° F (-29° to 65° C)

Part Number: **BSMK**

What's Included: TCM



Immediate pH testing is available in brilliant, long lasting colors. These direct-reading pH papers give a simple, single color match for all pH values in distinct, bright color separations. 100 dip sticks are packaged in a clear plastic case with a color chart.

Part Number: **BML-PH**

What's Included: 100 dip sticks, pH 1-14

**pH Test
Strips**



Ensuring adequate quality base feed stock is the key to successful biodiesel production. To determine the percentage of FFA's in your feedstock, simply dip the test strip into your oil and submerge for 2 seconds. Remove the strip and count the number of bands without any blue color.

Part Number: **BML-FFA**

What's Included: Box of 40 FFA percentage level indicator strips (>2% to >7%)

**FFA Test
Strips**